

AN-3100D Annunciator

FOR POWER GENERATION, TRANSMISSION & DISTRIBUTION, PETROLEUM, PETROCHEMICAL, AND OTHER PROCESS INDUSTRIES



INNOVATIVE ANNUNCIATOR

Continuing with the widely successful AN-3100 series of annunciators, AMETEK's new AN-3100D brings alarm monitoring to new levels. Time stamped alarms and more communication options are now available. Installation and setup have been simplified making this an ideal fit for new projects or system replacements. The unique software configuration provides more features and functions a mouse click away.

Time Stamped Alarms (SER)

All of your alarms can include a time stamp, synchronized by IRIG-B or our internal clock. This can be presented through Modbus, DNP, OPC or to a local printer or terminal for viewing. Dual ports (serial and Ethernet) can be provided for simultaneous connections to different devices.

Communications

Transmit or receive alarms using our RS-232/485 serial or Ethernet port. The AN-3100D supports Modbus and DNP protocols. Communicate via OPC using our OPC Server Software.


Software Configuration

While all systems are pre-configured to your specifications, the software configuration tool unleashes the true power of the AN-3100D.

You can select any operational sequence, sort alarms by group, configure your relay outputs and more. There is never any reason to pull out the front accessible input cards as changes can be made via software.

Compact Size

The annunciator and all electronics including the communication options are self contained within a compact frame less than seven inches deep. In most cases, the power supply is included inside the system simplifying installation and wiring.



Reliability

Every AN-3100D annunciator is equipped with low power, long life LEDs. The brightness exceeds standard incandescent bulbs and they last years longer. If a LED needs replacement, our automatic detector provides notice so critical alarms are not missed. A built-in ground fault detector is available for indicating ground faults in your field wiring.

Flexible Design

The window legends are printed on standard transparency film, making it easy to change legends at any time. The annunciator capacity can be increased with built-in expansion. All features and options are field selectable and upgradeable.

FEATURES AND BENEFITS

- Timed Stamped Alarms (SER)
- LED Illumination (Standard)
- Dual Communications: Serial and Multi-user Ethernet
- Modbus, DNP, OPC Protocols
- Software Configurable
- Laser Printed Legends
- Internal Self Diagnostics
- Compact Size

AMETEK[®]
POWER INSTRUMENTS

EXPERIENCE THE
POWER[™]

Experience the Power[™]

SPECIFICATIONS

INPUT

Field Contacts

- Normally Open (N.O.) or Normally Closed (N.C.) input selection through software or hardware
- Wetted (voltage supplied) or dry (voltage free) contacts

Field Contact Voltage

- 12, 24, 48, 125 VDC, 120 VAC jumper selectable (.0018mA per input)

Input Isolation

- Each input is optically isolated

Input Response

- 50 milliseconds (standard)
- 1 millisecond fast response (opt)
- 50 milliseconds to 250 seconds software adjustable

DISPLAY

LED

- White LED, minimum 2 per window

Window Sizes (h x w)

- Quad: 1.5 x 1.5 inch (38 x 38 mm)
- Third: 1.0 x 3.0 inch (25 x 76 mm)
- Half: 1.5 x 3.0 inch (38 x 76 mm)
- Full: 3.0 x 3.0 inch (76 x 76 mm)

Window Color

- White, red, yellow, amber, green, blue

Legends

- Laser printed on transparency film or engraved windows

ALARM SEQUENCE

Sequence Selections

- A, A4, M, R, R12, F1A, F3A, F2M1, FFAM2, F3C and R12C
- Software configurable
 - Dual color sequences
 - Customized flash rates
 - Up to 4 first out groups

CONTROLS

- Integral test, acknowledge, silence and reset with LED status lights
- External push button inputs
- Configurable switch inputs (inhibit LEDs, horns, relays)

OUTPUTS

Auxiliary Relay Option

- Individual or dual relay per point
- Follows field contact or alarm sequence
- Software configurable
- Energized/de-energized operation
- Form A or form B (N.O. or N.C.)
- Form C (SPDT)

Common Relays

- 2 relays included for: critical and non-critical horn; ringback audible

- 2 relays available for: critical and non-critical reflash, common alarm; watchdog, power fail, ground fault

- Software configurable
- Energized or de-energized operation
- Form A or form B (N.O. or N.C.)

Relay Ratings

- 24 VDC @ 3.0 amps
- 110 VDC @ 0.1 amps
- 120 VAC @ 3.0 amps

Audible

- Internal 80db @ 30cm audible device external horns available

COMMUNICATION

Modbus RTU and TCP/IP

- Master or slave
- Transmit or receive alarms
- RS-232/485 or Ethernet
- Pushbutton controls

DNP 3.0

- Slave mode
- Transmit alarms
- RS-232/485
- Pushbutton controls

OPC Server Software

- Ver. 2.0 OPC DA

Serial ASCII

- RS-232/485
- For local terminal/printer

TIME STAMPED ALARMS

- 1 or 4 msec time stamp resolution
- IRIG-B time sync input or internal clock
- Point #, alarm status, time and date
- Modbus, DNP, ASCII outputs
- 500 event storage

CONNECTIONS

Input/Output Terminals

- Fixed barrier terminal block, 12 GA (2.5mm) maximum, ring, spade or bare wire termination.

Communication Ports

- Serial: 9 pin female D connector
- Ethernet: RJ45 connector
- IRIG-B: BNC connector

POWER REQUIREMENTS

Internal or External Power Supplies

- 230 VAC (176-264 VAC 50 Hz)
- 120 VAC (88-132 VAC 60 Hz)
- 125 VDC (100-250 VDC)
- 48 VDC (38-58 VDC)
- 24 VDC (19-29 VDC)

Max. 1.7 watts/input @ power input

MECHANICAL

Mounting

- Semi-flush panel mounting
- 19 inch rack mounting
- Wall (surface) mounting
- NEMA enclosures

Weight

- 1.2 lbs per cell (0.34 kg per cell)

ENVIRONMENT

Operating Temperature Range:

- -4 to 122°F (-20 to 50°C)

Humidity:

- 20-95% RH

Surge Withstand:

- ANSI C37.90.1 (oscillatory)

Fast Transient:

- IEC-61000-4-4

Surge Immunity:

- IEC-61000-4-5

EMI/RFI/ESD:

- IEC-61000-4-3, 4-6, 6-3, 4-8, 4-2

Isolation:

- 1950 VDC or 1400 VAC input to output, logic, case

CERTIFICATIONS

UL, ULC, CE

FM Class 1, Div 2, FMC

Semi-flush Mounting Details inches (mm)

Cells H or W	Overall H or W	Panel Cut-Out H or W
1	5.0 (127)	4.06 (103)
2	8.47 (215)	7.53 (191)
3	11.94 (303)	11.00 (279)
4	15.40 (391)	14.47 (368)
5	18.88 (479)	17.94 (456)
6	22.34 (568)	21.41 (544)
7	25.81 (656)	24.88 (632)
8	29.28 (744)	28.34 (720)
9	32.75 (832)	31.81 (808)
10	36.22 (920)	35.29 (896)
11	39.69 (1008)	38.75 (984)
12	43.16 (1096)	42.22 (1072)
13	46.63 (1184)	45.69 (1160)
Depth behind panel: 6.75", 8" with rear cover		

Example: 2 H x 3 W has a cut-out height of 7.53 (191) and a cut-out width of 11.0 (279)



For Customer Support

AMETEK Power Instruments
255 North Union Street
Rochester, NY 14605
Tel: +1 585.263.7700
Fax: +1 585.454.7805
power.sales@ametek.com

U.S.A. Headquarters

AMETEK Power Instruments
50 Fordham Road
Wilmington, MA 01887
Tel: +1 978.988.4903
Fax: +1 978.988.4990
www.ametekpower.com
power.sales@ametek.com

European Headquarters

Unit 15, Lisburn Enterprise Centre
Ballinderry Road
Lisburn, Co Antrim, UK BT282BP
Tel: +44 (0) 28.9260.4100
Fax: +44 (0) 28.9260.4141
sales@ametekuk.com

Asia Pacific Headquarters

No. 43 Changi South Avenue 2
#04-01
Singapore 486164
Tel: +65 6484.2388
Fax: +65 6481.6588
sales@ametekasia.com

AMETEK Instruments India Pvt. Ltd.

1st Floor, Prestige Featherlite Tech Park
Plot 148, EPIP Phase II
Whitefield, Bengaluru 560 066
Tel: +91 80.67823252
Fax: +91 80.67823232
powersales.india@ametek.com

