


INTEGRAL PUSHBUTTON MODEL NO. 90PB36*

COMMON AUXILIARY RELAY WIRING


FOR CUSTOMER USE IF REQUIRED




RELAY CONTACTS RATED 4 AMPS AT 250VAC OR 5 AMPS AT 28VDC OR 120VAC AND 0.5 AMP AT 125VDC RESISTIVE LOAD.

NT2-24D AUDIBLE DEVICE WIRING

DIAGRAM SHOWS NOVATONE HORN WITH P1 TERMINAL BLOCK ON P.C. BOARD ATTACHED TO HORN (REF. DWG. 57100–48) FOR EARLIER VERSIONS WITH PIGTAIL LEADS, CONNECT BLACK TO OV, RED TO +24 AND BLUE TO FLASHER TERMINAL (REF. DWG. 57100–44).



TERMINAL GROUPING DIAGRAM



PAWLARM

APPD/DATE AHD 02/27/90


THIRD ANGLE PROJECTION

DWN. BY S. KUNCA

OPERATIONAL SEQUENCE "ASFR"								
INPUT STATUS	FIRST VISUAL	SUBSEQUENT VISUAL	AUDIBLE					
FIRST ALARM	FAST FLASH		ON					
SUBSEQUENT ALARM		STEADY-ON	ON					
SILENCE	FAST FLASH	STEADY-ON	OFF					
ACK	STEADY-ON	STEADY-ON	OFF					
RETURN TO NORMAL	OFF	OFF	OFF					
TEST	FAST FLASH		ON					

NOTES:

- IF A NEW ALARM OCCURS WHILE TESTING, POINT WILL INDICATE ALARM CONDITION (RE-ALARM) AFTER ACKNOWLEDGE PUSHBUTTON IS OPERATED.
- POINT WILL INDICATE ALARM WHEN TEST PUSHBUTTON IS OPERATED IF THE VISUAL INDICATOR IS OFF OR STEADY—ON.



REV	ECN NO.	BY	APPD	DATE	MATERIAL:				JNLESS CIFIED	Γ
00	7100-82	SK	AHD	02/27/90	FINISH:				CHES	l
01	11872	SK	most	6/15/01	USED ON/REF. DWG	EF. DWG DESCRIPTION DRAWING LIST DRAWING LIST		.X =	= .015	ľ
					91AS*			.XXX = .005		l
					92AS*			MILLIMETERS X.0 = 1.0		Ī
								0.X = 0.XX =		ľ
								ANGLES ±0'30'		Γ
								SCALE	INCH	l
					90450-AS2-1-01-01.dwg © 1990		NTS	(MM)		

PANALARM 1725 WESTERN DRIVE, WEST CHICAGO, IL., 60185, U.S.A. PHONE: 1-630-231-5900 FAX: 1-630-231-4502

CUSTOMER WIRING DIAGRAM AND SEQUENCE 'ASFR' INFORMATION FOR SERIES 90

SHEET 1 OF 1

DWG. NO.

90450-AS2-1

-B-