

P&QR Power Quality Recorder

FOR POWER QUALITY, LOAD STUDIES, AND FLICKER ANALYSIS AT POWER PLANTS, SUBSTATIONS, AND OTHER FACILITIES



POWER AND QUALITY RECORDER

AMETEK Power and Quality Recorders (P&QR) provide high performance power quality recording at an affordable price. For the electrical utility, this is an economical way to monitor power system disturbances on the power distribution grid for all your key accounts.

For the facilities manager or power quality department, this is an excellent tool for monitoring power quality in a plant to prevent costly shutdowns and work stoppages. The versatile P&QR comes in a portable case, wall mount box or a 19-inch rack mount chassis to meet any application: indoors or outdoors; portable or permanent. The P&QR recorder has high performance 14-bit resolution with 128 samples/cycle recording. A massive 6.4 GB of memory is included for trend recording up to 16 weeks and waveform capture up to two seconds. The P&QR features high-speed Ethernet and Modem communications, battery back-up, and a suite of available software applications.



FEATURES AND BENEFITS

- Power quality monitor—measures voltage and frequency profiles, voltage dips and surges, loss of supply, harmonic content, flicker, voltage and current imbalance
- Transient fault recorder—analogue inputs are sampled at up to 128 samples per cycle with a maximum record length of 2 seconds
- Disturbance Recorder/Logger—analogue inputs are sampled at up to 2 samples per cycle with RMS measurements recorded up to one minute
- Trend Recording—input and computed quantities are logged as maximum, minimum, and average quantities every minute for up to 16 weeks.
- Remote Capabilities—via Ethernet or modem, and the process can be automated using the recorder's Auto-Call or Auto-Poll features
- Software—wide range of application software for communicating, configuring, downloading, displaying and analyzing recorded data. Auto-Poll/Call automates the complete process of retrieving your recorded data

AMETEK[®]

**POWER
INSTRUMENTS**

Experience the Power™

SPECIFICATIONS

INPUTS

Number of channels

- 8 (4 voltage, 4 current) consult factory for other configurations

Voltage Inputs

- 150/300/600 RMS maximum, Star (wye) or delta connections

Current Inputs

- 1/5/100/200/500/1000 A RMS nominal thru external CTs. designed to record to 40% over-range

Frequency Response

- 40Hz-3kHz. (+0dB, -3dB for voltages) DC-3kHz (+0dB for currents)

Accuracy

- Better than 0.2% of full scale

RECORDING

Resolution

- 14 bits

Sample Rate

- 128 sample per cycle, 50/60 HZ (6.4/7.68k samples per second)

DATA STORAGE

Hard Disk

- 6.4 GB (up to 1000 events/surveys)

RECORDED DATA

Waveform Capture

- 4 cycles pre, 12 cycles post at 128 samples/cycle (Option for up to 2 seconds)

Disturbance Recording

- Up to 1 minute of RMS data at 2 samples/cycle

Trending (up to 16 weeks)

- Voltage, Current, Frequency, Watts—1 minute min./max./avg.
- Harmonics —10 minute min./max./avg./angle to the 50th harmonic

- Imbalance —10 minute min./max./avg.

- Flicker—10 minute Pst

Computed (at PC)

- Phase angle, power factor, and sequence components

EVENT TRIGGERING

Trigger Parameters

- Over/under level with hysteresis. Rate of Change and THD

Accuracy

- Better than 2%

External Trigger Relay Contact

- 24-120 VDC nominal

POWER SUPPLY

Input Voltage Range

- 100 to 300 VDC, 85 to 264 VAC, 50/60Hz (24 or 48 VDC nominal)

Power Requirement

- 20 VA

Battery (Optional)

- 15 minute ride-through

REAL TIME CLOCK

Clock Source

- 32,768 Hz internal crystal oscillator

Resolution

- 1 ms

Range

- Time and date (including leap year and day of the year)

Synchronization

- 50/60 Hz from voltage input

COMMUNICATIONS

Serial Port

- RS232 type. Speed up to 57.6 kBaud

Modem (optional)

- Hayes compatible internal type (up to 57.6 kBaud)

Network (optional)

- TCP/IP 10Base2 or 10BaseT

VOLTAGE WITHSTAND

Isolation, Impulse Voltage Withstand, Electrical Fast Transient (EFT), Surge Withstand (SWC), RFI and ESD to IEEE/IEC Standards

ENCLOSURE

Mounting

- Wall (internal terminals) — 11.75 in. x 16.0 in. x 8.25 in. (300 mm x 400 mm x 210 mm)

- 19" Rack Mounting — 13.25 in. x 19.0 in. x 5.25 in. (336 mm x 482 mm x 133 mm)

- Portable —

- 14.25 in. x 13.75 in. x 5.25 in. (362 mm x 349 mm x 133 mm)

Weight

- 13.2-17.6 lbs. (6-8 kg) depending on enclosure style

ENVIRONMENT

Operating Temperature

- 14° to 122°F (-10° to 50°C)

Storage Temperature

- -40° to 158°F (-40° to 70°C)

Humidity

- 5 – 95% RH (non condensing)

CERTIFICATION

CE



For customer support call:

POWER INSTRUMENTS

255 North Union Street
Rochester, NY 14605
Tel: 585.263.7700
Fax: 585.454.7805
power.sales@ametek.com

HEADQUARTERS

AMETEK Power Instruments
50 Fordham Road
Wilmington, MA 01887
Tel: 978.988.4903
Fax: 978.988.4990
power.sales@ametek.com

EUROPEAN HEADQUARTERS

Unit 20, Ridgeway
Donibristle Industrial Estate
Dalgety Bay, Dunfermline, KY119JN
Scotland U.K.
Tel: 44.1383.825630
Fax: 44.1383.825715
power.sales@ametek.com

ASIA PACIFIC HEADQUARTERS

10 Ang Mo Kio Street 65
#05-12 Techpoint
Singapore 569059
Tel: 65.6484.2388
Fax: 65.6481.6588



ISO 9001 Certified